

LABDex



Digital Tube Roller LX529DTR

Email: info@labdex.com **website:** www.labdex.com

Description

Digital Tube Roller LX529DTR is a compact unit designed for gentle to thorough mixing with continuous working mode. Equipped with one operational mode with adjustable speed and compatibility with various sizes of tubes and quantity of 6 rollers.

Specifications

Operation mode	Rolling
Speed range	5 rpm ~ 80 rpm
Roller Quantity	6
Roller length	280 mm
Maximum load	4 kg
Time range	1 min ~ 99 hr 59 min
Fuse	250 V, 1 A, ϕ 5 × 20
Power	25 W
Power supply	AC 100 ~ 243 V, 50 / 60 Hz
Dimension	450 x 260 x 120 mm
Net weight	3.7 kg
Packing dimension	570 x 360 x 200 mm
Gross weight	5 Kg

Features

- ˆ LED display to show speed and time
- ˆ Continuous working mode
- ˆ Operation mode: Rolling type
- ˆ Adjustable operational speed with maximum speed of 80rpm
- ˆ Compatible with a range of tube sizes
- ˆ Came with stable performance motor that gives low noise and long use life
- ˆ Time and speed display on LED screen

Applications

- Used in mixing blood sample, sticky substance and solid-liquid suspension, immunoprecipitation and prevention of blood clots



71-75 Shelton Street Covent Garden, London WC2H 9JQ UK.

Email: info@labdex.com | Website: www.labdex.com